

# FX SERIES

Sanitary & Food Grad Applications

- Better Clarity of Liquid Stream
- Ultra-Fine Particle Separation
- CIP Wash/Sanitization System
- Available in 2 or 3 Phase Configurations
- Surface Finishes up to 3A



## Common Applications

- Dairy Processing
- Avocado Oil Processing
- Olive Oil Processing
- Soy Processing
- Vegetable Oil Processing
- Juice Manufacturing
- Protein Extraction
- Starches
- Pharmaceutical Manufacturing
- Fish Processing
- Cassava Starch Processing
- Instant Coffee Production
- Lactose Manufacturing
- Casein Manufacturing
- Fermentation Broths
- Lupin Protein Extraction
- Limed Fleshing
- Maize Starch Production
- Palm Oil Extraction
- Much More...





# FX SERIES



## FX Series Specs.

Unit	Feed Capacity	Phase	Empty Decanter Weight	Beach Angle	Total Installed Power	Bowl Diameter
<b>FX100</b>	0.5-2 M3/h (3-44 gpm)	2 or 3	318 kg (700 lbs)	10°   8°	7hp	152 mm (6")
<b>FX200</b>	1-10 M3/h (3-44 gpm)	2 or 3	900 kg (1984 lbs)	10°   8°	15hp	254 mm (10")
<b>FX300</b>	5-14 M3/h (20-60 gpm)	2 or 3	1752 kg (3800 lbs)	10°   8°	40hp	356 mm (14")
<b>FX400</b>	17-30 M3/h (75-125 gpm)	2 or 3	4200 kg (9259 lbs)	10°   8°	65hp	457 mm (18")
<b>FX500</b>	35-55 M3/h (154-242 gpm)	2 or 3	6500 kg (14330 lbs)	10°   8°	120hp	559 mm (22")
<b>FX600</b>	45-90 M3/h (200-400 gpm)	2 or 3	9700 kg (21385 lbs)	10°   8°	150hp	660 mm (26")
<b>FX700</b>	68-159 M3/h (300-700 gpm)	2 or 3	15800 kg (34833 lbs)	10°   8°	200hp	762 mm (30")